

MI3 II o

GRZ 0,6
GFZ 1,2
THmax./WHmax. 7,5 m
GHmax. 12,0 m
SD 35°- 45°
FD

MI2 II

GRZ 0,6
GFZ 1,2
THmax./WHmax. 7,5 m
GHmax. 12,0 m
SD 35°- 45°
FD

MI1* (§1(10) BauNVO)

MI1 II-III

GRZ 0,6
GFZ 1,2
THmax. 9,5 m
GHmax. 12,0 m
SD/WD 20°- 40°

MI3 II o

GRZ 0,6
GFZ 1,2
THmax./WHmax. 7,5 m
GHmax. 12,0 m
SD 35°- 45°
FD

WA1 III o

GRZ 0,4
GFZ 1,1
THmax. 9,5 m
GHmax. 12,0 m
SD/WD 20°- 40°

WA2* (§1(10) BauNVO)

WA2 II o

GRZ 0,4
GFZ 0,8
THmax. 6,5 m
GHmax. 12,0 m
SD/WD 30°- 45°

WA2 II o

GRZ 0,4
GFZ 0,8
THmax. 6,5 m
GHmax. 12,0 m
SD/WD 30°- 45°

Flur 10

Flur 6

Maßstab 1: 1.000

